



Centurion™ C2-A

Two Cylinder Fully Automatic Gas Cabinet with 1 x 1 Enclosure



SEMI-GAS® supplies SEMI S2 certified, production-ready ultra high purity gas source systems, distribution systems and control technology to leaders in the Semiconductor industry and related high-tech fields. Built to address the most rigorous precision and purity demands of these specialized applications, SEMI-GAS® solutions are globally renowned for their premier levels of safety, quality, and performance.

DESIGN STANDARDS

- ◆ Conforms to SEMI S2 Standards
- ◆ UL Labeled
- ◆ Conforms to Uniform Building and Fire Codes
- ◆ Upholds Sample Validation Testing Standards
- ◆ Helium Leak Tested to 1×10^{-9} atm-cm³/sec
- ◆ Equipped with GigaGuard™ PLC Controller

FEATURES

- ◆ Safely Dispenses Hazardous Process Gases
- ◆ Separate Enclosures for Individual Cylinders
- ◆ Performs Purging Automatically
- ◆ Automatic Shutdown in the Event of an Alarm Trip
- ◆ Includes Ergonomically Positioned Color Touch Screen
- ◆ Intuitive Operating Interface and Control
- ◆ Continuously Monitors System Conditions for Alarms
- ◆ Maintains Detailed Alarm Logs
- ◆ Multiple Communications Protocols Available
- ◆ Optional Z-Purge
- ◆ Optional 1CE200 Enclosures Specifically Designed for Silane Delivery

ENGINEERING DATA

- ◆ Dimensions: 86" T X 31" W X 23" D
- ◆ Exhaust Duct- 1CE200: 8" Diameter
- ◆ Exhaust Duct- 1CE: 6" Diameter
- ◆ Window Open Duct Flow- 1CE200: 850 SCFM
- ◆ Window Open Duct Flow- 1CE: 350 SCFM
- ◆ Voltage: 110 to 240 VAC, 1 Phase
- ◆ Frequency: 50 to 60 Hz

MATERIALS OF CONSTRUCTION

- ◆ Welded 11 Ga Steel Enclosure
- ◆ Self-Closing and Self-Latching Door
- ◆ Self-Closing and Lockable Window
- ◆ Heavy Cast Aluminum Cylinder Brackets
- ◆ Polycarbonate Face Shield
- ◆ Durable, Corrosion Proof, Non-Skid Floor Mat
- ◆ UL Approved Fire Sprinkler
- ◆ 1/4" Thick Safety Glass Window



ORDERING INFORMATION

Contact your SEMI-GAS® sales rep or visit www.semi-gas.com

BY APPLIED ENERGY SYSTEMS

180 Quaker Lane
Malvern, PA 19355

Phone: 610.647.8744

Fax: 610.640.4548

Email: sales@semi-gas.com

CENTURION-C2-A-1x1-082016-V1

SAFETY FEATURES

- ◆ **Coaxial Tubing** for toxic and hazardous gas applications (optional)
- ◆ **Door Switch Monitor** for applications that require extra security and/or limited access (optional)
- ◆ **UV/IR Detector** for pyrophoric gas applications including silane and silane mixtures greater than 1.37% (required for silane)
- ◆ **Rate of Rise Heat Detector** for flammable gas applications (optional)
- ◆ **Hazardous Gas Detector** for all hazardous, toxic, and/or flammable gas applications (required for silane, consult local codes for all other gases)
- ◆ **Purge Gas Bleed Valve** for manifolds and piping systems with large internal volumes or line lengths (optional)
- ◆ **Controller Z-Purge Kit** for systems installed in Class 1 Division 2 hazardous locations, as well as applications for silane and silane mixtures greater than 1.37% (required for silane)
- ◆ **Dual Cylinder Restraints** for applications that require additional cylinder security or are located in seismic zones (required for specific seismic areas)
- ◆ **Auto-Guard™ Cylinder Connection Cover** for preventing accidental disconnection of a hazardous gas cylinder from a gas source manifold (optional)
- ◆ **Shutboy Software Upgrade** to accommodate Shutboy valve shutters for automatically closing the gas cylinder valve during emergency situations (optional)

ORDERING INFORMATION

Example: Two Cylinder Fully Automatic Autoswitchover Gas Cabinet with Individual Process Cabinets



Product

C = Centurion™ Gas Cabinet

Configuration

1 = 1 Cylinder
2 = 2 Cylinder
3 = 3 Cylinder

Control

M = Manual
S = Semi Automatic
A = Fully Automatic

Process Manifold

2 = 2-Valve (for inert gases)
3 = 3-Valve (for inert gases)
5 = 5-Valve (for toxic, flammable, and reactive gases)

Operation

X = Autoswitchover
N = Independent Processes

Purge

P = Purge
O = No Purge

Option

I = Individual Process Cabinets
S = System Upgrades for Silane

*All Centurion™ Gas Cabinets can be customized to meet unique specifications. Contact your SEMI-GAS® sales rep for details.

