



## SEMI-GAS® EQUIPMENT

### Xturion™ Custom Gas Equipment

### Hybrix™

#### Features

- Combines Source and Distribution Functionality
- Incorporates Multiple Source Systems in One
- Distributes Gases from Internal or External Source Supplies
- Safely Dispenses Hazardous Process Gases
- Performs Purging Automatically
- Includes Ergonomically Positioned Color Touch Screen
- Continuously Monitors System Conditions for Alarms
- Intuitive Operating Interface and Control
- Multiple Communications Protocol Available



#### Engineering Data

- Dimensions: 86" T x 40" W x 23" D
- Exhaust Duct: 2 w/ 6" Diameters
- Window Open Duct Flow: 2 w/ 350 SCFM
- Voltage: 110 to 240 VAC, 1 Phase
- Frequency: 50 to 60 Hz

#### Ordering Information

Contact your SEMI-GAS® Sales Representative  
or call 610-647-8744

#### Materials of Construction

- Welded 11 Ga Steel Enclosure
- Self-Closing and Self-Latching Door
- Self-Closing and Self-Latching Window
- Polycarbonate Face Shield
- Durable, Corrosion Proof, Non-Skid Floor Mat
- UL Approved Fire Sprinkler
- 1/4" Thick Safety Glass Window

